

# COMPACT FLOOR®

Wärmeleitschichten · Conductive Layers

## Flooring

### CompactFloor® DIRECT 1.5

Lay CompactFloor® DIRECT 1.5 according to the installation instructions. Adhere joints with aluminum tape for sealing (vapour barrier).

Dry construction on underfloor heating | insulation layer

in case of direct installation on heating element with CompactFloor® DIRECT 1.5

Parquet	Parquet floating installation ≥ 15 mm
---------	---------------------------------------

on conductive layer CompactFloor® PRO 12

Parquet	Parquet floating installation
---------	-------------------------------

Laminate	Laminate floating installation
----------	--------------------------------

Cork	Cork floating installation
------	----------------------------

on conductive layer CompactFloor® EXPERT 20

Parquet	Parquet floating installation
---------	-------------------------------

Laminate	Laminate floating installation
----------	--------------------------------

Cork	Cork floating installation
------	----------------------------

on screed

Parquet	Parquet floating installation
---------	-------------------------------

Laminate	Laminate floating installation
----------	--------------------------------

Cork	Cork floating installation
------	----------------------------

Status 01 | 2017 – Pay attention to all manufacturer details and laying instructions! © Compact Floor GmbH – www.compact-floor.com

CompactFloor® DIRECT